

IN THE CLAIMS:

1-6. (Canceled)

7. (Previously Presented) An endless drive track for a snowmobile, comprising a base and traction lugs integrally formed with the base, the traction lugs extending upward from the base and extending across substantially all of a width of the base, wherein the traction lugs are inclined relative to normal to the base and wherein the traction lugs comprise a first set of traction lugs inclined away from a track travel direction and a second set of travel lugs inclined toward a track travel direction.

8-11. (Canceled)

12. (Currently Amended) An endless drive track for a snowmobile, the track having an outer periphery comprising:

a base including an outer side; and

traction lugs extending outward from the outer side of the base, each of said lugs having a width extending across a substantial portion of a width of the base, the lugs comprising a lower portion having a first angle of inclination relative to normal to the base and an upper portion having a second angle of inclination relative to normal to the base, the second angle being greater than the first angle.

13. (Previously Presented) The endless drive track of claim 12, wherein the first angle of inclination is in the range from 5 to 45 degrees.

14. (Previously Presented) The endless drive track of claim 13, wherein the first angle is in the range from 5 to 30 degrees.

15. (Previously Presented) The endless drive track of claim 13, wherein the first

25315

CUSTOMER NUMBER

- 2 -

ACAS-I-10372ROA

BLACK LOWE & GRAHAM PLLC


701 Fifth Avenue, Suite 4800
Seattle, Washington 98104
206.381.3300 • F: 206.381.3301

angle is in the range from 5 to 15 degrees.

16. (Previously Presented) The endless drive track of claim 12, wherein there is an inflection point between the upper and lower portion.

17. (Currently Amended) ~~The endless drive track of claim 12, a~~An endless drive track for a snowmobile, the track having an outer periphery, the track comprising:

a base including an outer side; and

traction lugs extending outward from the outer side of the base, the lugs comprising a lower portion having a first angle of inclination relative to normal to the base and an upper portion having a second angle of inclination relative to normal to the base, the second angle being greater than the first angle;

wherein the lower portion has a first leading face having a first leading face angle and the upper portion has a second leading face having a second leading face angle, the first leading face angle being about 14 degrees and the second leading face angle being about 20 degrees.

18. (Currently Amended) ~~The endless drive track of claim 12, a~~An endless drive track for a snowmobile, the track having an outer periphery, the track comprising:

a base including an outer side; and

traction lugs extending outward from the outer side of the base, the lugs comprising a lower portion having a first angle of inclination relative to normal to the base and an upper portion having a second angle of inclination relative to normal to the base, the second angle being greater than the first angle;

wherein the lower portion has a trailing face having a first trailing face angle and wherein the upper portion has a trailing face having a second trailing face angle, the first trailing face angle being about equal to 3 degrees and the second trailing face angle being about equal to 11 degrees.

25315

CUSTOMER NUMBER

- 3 -

ACAS-I-10372ROA

BLACK LOWE & GRAHAM PLLC



701 Fifth Avenue, Suite 4800
Seattle, Washington 98104
206.381.3300 • F: 206.381.3301

19. (Previously Presented) A method for using an endless track, the method comprising:

providing a snowmobile;

providing a track comprising

a base; and

traction lugs integrally formed with the base, the traction lugs extending upward from the base and extending across substantially all of a width of the base, the traction lugs being inclined relative to normal to the base; and

selectively securing the track to the snowmobile with one of having the traction lugs inclined toward a track direction of travel and having the traction lugs inclined away from the track direction of travel.

20. (Previously Presented) The method of claim 19, wherein the track bears indicia indicating orientations of the traction lugs suitable for hill climbing and deep snow; the selected track lug orientation being based on the intended use of the track in conjunction with the indicia formed on the track.

25315

CUSTOMER NUMBER

- 4 -

ACAS-I-10372ROA

BLACK LOWE & GRAHAM PLLC



701 Fifth Avenue, Suite 4800
Seattle, Washington 98104
206.381.3300 • F: 206.381.3301